

TROUBLESHOOTING

- Cloudy or Colored Water — Cloudy appearance in treated water is caused by air bubbles trapped in water. This does not affect cartridge performance and will disappear with use.
- Flakes In Cold Water Or Ice —Concentrations of minerals in water will form particles when water becomes frozen and melts.
- Slow water flow rate — Cartridge has reached its capacity. Replace cartridge.
- Low Water Pressure — Confirm water pressure at unit without filter installed is a minimum of 35 psi (244 kPa). Correct water pressure.
- Unusual Taste — Cartridge has reached its capacity. Replace cartridge.
- Black Particles in Ice Cubes — Initial water ejected through cartridge may contain black particles of harmless carbon dust flushed from cartridge.

REPLACEMENT WATER FILTER LIMITED WARRANTY

Maytag Appliances will repair or replace, free of charge, any part which is defective due to workmanship or materials for:

- Multistage cartridge: 6 months from date of purchase when defect is due to workmanship or materials.

Warranty Limitations

- Not responsible for replacement caused by local poor water quality.
- Begins at date of original purchase.
- Applies to product used within the United States.
- Service must be performed by an authorized Amana technician.

Warranty if Void If

- Product is used on a commercial, rental or leased basis.
- Product has defect or damage due to product accident, alteration, fire, flood, lightning, shipping and handling or other conditions beyond the control of Maytag Appliances.
- Product is improperly installed or used.

Owner's Responsibilities

- Provide proof of purchase (sales receipt).
- Provide normal care and maintenance.
- Replace owner replaceable items where directions appear in Installation and Operating Instructions.

In No Event shall Maytag Appliances be liable for incidental or consequential damages.

This warranty gives you specific legal rights and you may have others which vary from state to state. For example, some states do not allow the exclusion or limitation of incidental or consequential damages so this exclusion may not apply to you.

HOW DO I ORDER A REPLACEMENT FILTER CARTRIDGE?

To purchase replacement water filter cartridges, visit your local dealer or parts distributor. In the U.S., you may also call 1-800-901-2042 and ask for filter 67003662. Outside the U.S., contact your local appliance dealer or parts distributor.

IMPORTANT:

Condition of water and amount used determines life span of water filter cartridge. If water use is high, or if water is of poor quality, replacement may need to take place more often.

Water Filter Data

System specification and Performance Data Sheet for Replacement Water Filter Cartridge Model 67003662

SAFETY INFORMATION

Read, understand, and follow all safety information contained in these instructions prior to installation and use of this Replacement Water Filter Cartridge Model 67003662. Retain these instructions for future reference.

Intended use:

This Replacement Water Filter Cartridge Model 67003662 is intended for use in filtering potable water in the Amana Clean 'n Clear retractable water filtration system, and has not been evaluated for other uses.


**IMPORTANT**

To reduce the risk associated with the ingestion of contaminants: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. EPA Establishment 10350-MN-005.


**IMPORTANT**

To reduce the risk associated with property damage due to water leakage:

- Read and follow** Use Instructions before installation and use of this system.
- Installation and use must comply with all state and local plumbing codes.
- Protect from freezing**, remove filter cartridge when temperatures are expected to drop near or below freezing.
- If water filtration system has been allowed to freeze, replace filter cartridge.**
- Do not install on hot water supply lines.** The maximum operating water temperature of this filter system is 100°F (37.7°C).
- Do not install** if water pressure exceeds 120 psi (827 kPa). If your water pressure exceeds 80 psi, you must install a pressure limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.
- Do not install** where water hammer conditions may occur. If water hammer conditions exist you must install a water hammer arrester. Contact a plumbing professional if you are uncertain how to check for this condition.
- If system has not been used for several months, and water has an unpleasant taste or odor, flush system by dispensing 2-3 glasses of water. If unpleasant taste or odor persists, change filter cartridge.
- The disposable filter cartridge should be replaced at least every 6 months.

REPLACING THE WATER FILTER

Cartridge needs to be replaced after 750 gallons of water (2,839 liters) or 6 months of use, whichever comes first. Local water quality may affect rated life of filter.

1. Protect floor from possible water spill.
2. Turn cartridge counterclockwise until it releases from filter head.
3. Pull cartridge down and discard.
4. Inspect O-rings on head for visible damage or wear. Replace with part no. RO185015 if necessary.
5. Write date of installation on replacement cartridge.
6. Push new cartridge into head.
7. Turn cartridge clockwise until it stops.
8. Flush 3.9 gallons through filter before use (flush approximately 3 minutes). Discard the first three batches of ice after replacing cartridge.

Manufactured by:  
3M Purification Inc.  
400 Research Parkway  
Meriden CT 06450

© 2011 3M Company. All rights reserved.  
NSF is a trademark of NSF International.  
  
101088 0311

Performance Data Sheet

Models: RO185011 Using Replacement Cartridge: 67003662

Read this Performance Data Sheet and compare the capabilities of this unit with your actual water treatment needs.

Note that while the testing was performed under standard laboratory conditions, actual performance may vary. Systems must be installed and operated in accordance with manufacturer’s recommended procedures and guidelines.

The Amana Clean ‘n Clear retractable water filtration system uses a 67003662 replacement cartridge. Timely replacement of filter cartridge is essential for performance satisfaction from this filtration system. Please refer to the applicable section of your owner’s manual for general operation, maintenance requirements and trouble-shooting.

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42 and Standard 53.



System tested and certified by NSF International against NSF/ANSI Standard 42 and Standard 53 for the reduction of substances listed below.

Capacity 750 Gallons (2,839 Liters) Contaminant Reduction Determined by NSF testing.

| Contaminant Reduction                         | Average Influent  | NSF/ANSI Specified Challenge Concentration                                       | Avg % Reduction | Average Product Water Concentration | Max Permissible Product Water Concentration | NSF Reduction Requirements | NSF Test Report |
|-----------------------------------------------|-------------------|----------------------------------------------------------------------------------|-----------------|-------------------------------------|---------------------------------------------|----------------------------|-----------------|
| Chlorine Taste and Odor                       | 2.0 mg/L          | 2.0 mg/L ± 10%                                                                   | 97.5%           | 0.05 mg/L                           | N/A                                         | ≥ 50%                      | J-00056501      |
| Nominal Particulate Class I, ≥0.5 to < 1.0 µm | 13,666,667 pts/mL | At least 10,000 particles/mL                                                     | 98.9%           | 143,333 pts/mL                      | N/A                                         | ≥85%                       | J-00056506      |
| Asbestos                                      | 96 MFL            | 10 <sup>7</sup> to 10 <sup>8</sup> fibers/L; fibers greater than 10 µm in length | 99.99%          | <1 MFL                              | N/A                                         | ≥ 99%                      | J-00056511      |
| Atrazine                                      | 0.010 mg/L        | 0.009 mg/L ± 10%                                                                 | 89.3%           | 0.001 mg/L                          | 0.003 mg/L                                  | N/A                        | J-00056512      |
| Benzene                                       | 0.014 mg/L        | 0.015 mg/L ± 10%                                                                 | 96.3%           | 0.005 mg/L                          | 0.005 mg/L                                  | N/A                        | J-00056535      |
| Carbofuran                                    | 0.08 mg/L         | 0.08 mg/L ± 10%                                                                  | 86.6%           | 0.01 mg/L                           | 0.04 mg/L                                   | N/A                        | J-00056537      |
| Cyst*                                         | 122,500 cysts/L   | Minimum 50,000 cysts/L                                                           | 99.99%          | 1 cyst/L                            | N/A                                         | ≥99.95%                    | J-00056513      |
| Lead @ pH 6.5                                 | 0.153 mg/L        | 0.15 mg/L ± 10%                                                                  | 99.3%           | 0.001 mg/L                          | 0.010 mg/L                                  | N/A                        | J-00056515      |
| Lead @ pH 8.5                                 | 0.150 mg/L        | 0.15 mg/L ± 10%                                                                  | 99.3%           | 0.001 mg/L                          | 0.010 mg/L                                  | N/A                        | J-00058784      |
| Lindane                                       | 0.002 mg/L        | 0.002 mg/L ± 10%                                                                 | 97.8%           | 0.00004 mg/L                        | 0.0002 mg/L                                 | N/A                        | J-00058969      |
| Mercury @ pH 6.5                              | 0.006 mg/L        | 0.006 mg/L ± 10%                                                                 | 95.0%           | 0.0003 mg/L                         | 0.002 mg/L                                  | N/A                        | J-00058785      |
| Mercury @ pH 8.5                              | 0.006 mg/L        | 0.006 mg/L ± 10%                                                                 | 88.1%           | 0.0007 mg/L                         | 0.002 mg/L                                  | N/A                        | J-00058783      |
| P-Dichlorobenzene                             | 0.215 mg/L        | 0.225 mg/L ± 10%                                                                 | 99.7%           | 0.0005 mg/L                         | 0.075 mg/L                                  | N/A                        | J-00056538      |
| Toxaphene                                     | 0.015 mg/L        | 0.015 mg/L ± 10%                                                                 | 93.2%           | 0.001 mg/L                          | 0.003 mg/L                                  | N/A                        | J-00056531      |
| Turbidity                                     | 10.8 NTU          | 11 ± 1 NTU                                                                       | 98.7%           | 0.13 NTU                            | 0.5 NTU                                     | N/A                        | J-00058972      |

\* Based on the use of Cryptosporidium parvum oocysts

SPECIFICATIONS

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Service Flow Rate (Maximum)           | 0.78 gpm (2.9 lpm)                             |
| Rated Service Life RO185011 (Maximum) | 750 gallons (2,839 liters)                     |
| Minimum Operating Temperature         | 33°F (0.6°C)                                   |
| Maximum Operating Temperature         | 100°F (38°C)                                   |
| Minimum Pressure Requirement          | 35 psi (138 kPa)                               |
| Maximum Operating Pressure            | 120 psi (827 kPa)                              |
| Capacity:                             | Certified for up to 750 gallons (2,839 liters) |

State of California  
Department of Public Health  
Water Treatment Device  
Certificate Number  
10 - 2026  
Date Issued: April 5, 2010

|                                                                                                                                                                                                                                            |                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Trademark/Model Designation<br>RO185011                                                                                                                                                                                                    | Replacement Elements<br>67003662                                   |
| Manufacturer: Cuno, Inc.                                                                                                                                                                                                                   |                                                                    |
| The water treatment device(s) listed on this certificate have met the testing requirements pursuant to Section 116830 of the Health and Safety Code for the following health related contaminants:                                         |                                                                    |
| Microbiological Contaminants and Turbidity<br>Cysts<br>Turbidity                                                                                                                                                                           | Inorganic/Radiological Contaminants<br>Asbestos<br>Lead<br>Mercury |
| Organic Contaminants<br>Atrazine<br>Benzene<br>Carbofuran<br>p-Dichlorobenzene<br>Lindane<br>Toxaphene                                                                                                                                     |                                                                    |
| Rated Service Capacity: 750 gal                                                                                                                                                                                                            | Rated Service Flow: 0.78 gpm                                       |
| Conditions of Certification:<br>Do not use where water is microbiologically unsafe or with water of unknown quality, except that systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. |                                                                    |